




SM



- Operating Temperature: -40 ~ +140
- Insert: Brass. Steel with Zn coating
- Material: SMC(Sheet Moulding Compound)
- Colour,Insert,material In capability accordance with customer needs

SM BUS BAR INSULATOR

■ **SM-20 (mm)**

Tensile strength(LBS)	300
Voltage withstand(KV)	5
Torque strength(FT LBS)	4
screw(mm)	5
screw depth(mm)	7

■ **SM-25S (mm)**

Tensile strength(LBS)	400
Voltage withstand(KV)	6
Torque strength(FT LBS)	5
screw(mm)	6
screw depth(mm)	8

■ **SM-25 (mm) 34025**

Tensile strength(LBS)	500
Voltage withstand(KV)	6
Torque strength(FT LBS)	6
screw(mm)	6
screw depth(mm)	9

■ **SM-30 (mm)**

Tensile strength(LBS)	550
Voltage withstand(KV)	8
Torque strength(FT LBS)	8
screw(mm)	8
screw depth(mm)	11

■ **SM-35 (mm) 34035**

Tensile strength(LBS)	600
Voltage withstand(KV)	10
Torque strength(FT LBS)	10
screw(mm)	8
screw depth(mm)	11

■ **SM-40 (mm) 34040**

Tensile strength(LBS)	650
Voltage withstand(KV)	12
Torque strength(FT LBS)	12
screw(mm)	8
screw depth(mm)	11

■ **SM-45 (mm)**

Tensile strength(LBS)	1000
Voltage withstand(KV)	14
Torque strength(FT LBS)	20
screw(mm)	8
screw depth(mm)	11

■ **SM-51 (mm) 34051**

Tensile strength(LBS)	1000
Voltage withstand(KV)	15
Torque strength(FT LBS)	20
screw(mm)	8
screw depth(mm)	14

■ **SM-60 (mm)**

Tensile strength(LBS)	1200
Voltage withstand(KV)	20
Torque strength(FT LBS)	35
screw(mm)	10
screw depth(mm)	15

■ **SM-76 (mm) 34076**

Tensile strength(LBS)	1500
Voltage withstand(KV)	25
Torque strength(FT LBS)	40
screw(mm)	10
screw depth(mm)	20