

ODE-3-120043-301X (HP)

Optidrive E3 VFD Datasheet

1 HP, 4.3 A, 200-240 V, 3PH,
 IP66 Indoor Non-switched Variable Frequency Drive

Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	5.6 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	1 HP
Output Voltage	0 – Supply Voltage
Output Current	4.3 A

Cable Information

Max Supply Cable Size	0.31 in
Max Motor Cable Size	0.31 in
Max motor cable length	328 ft

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	No Internal Brake Transistor
Enclosure	IP66 Indoor Non-switched

Installation Options & Peripherals

- ▶ Communication Interfaces
- ▶ EMC Filters
- ▶ I/O Options
- ▶ Input Chokes
- ▶ Optistick Smart
- ▶ Output Filters
- ▶ Remote Keypads
- ▶ RJ45 Accessories
- ▶ USB PC Connection Kit



Dimensions



Size	1
Height	9.13 in
Width	6.34 in
Depth	7.05 in
Weight	6.84 lb(s)
Packaged Weight	7.56 lb(s)
Fixings	4 x M4